

TURBOVAC THERMOFORMERS:

WORLDCLASS THERMOFORMER FOR FLEXIBLE AND RIGID FILM

- > **Film widths:** **285 - 320 - 355 - 420 mm**
- > **Strokes:** **240 - 270 - 300 mm**

The range of thermoformers has been designed to satisfy the requirements of small to medium size processing operations that require the best value for their money in performance, hygiene, quality, reliability, serviceability and durability. The intuitive, user friendly control system makes programming easy, provides relevant management information and safeguards proper operation. All parts are very accessible for easy service and cleaning. The uncompromising choice of quality materials and design makes us proud to be able to offer this range of thermoformers.



Standard

- > Display prepared for remote connection and control through Ethernet; for example for software updates
- > Synchronisation for peripheral devices such as a labeler, printer, filler or loading robot
- > Control cabinet heating to prevent condensation on electrical circuits

Optional

- | | | | |
|-----------------|--------------|--------------------|--------|
| | 1 | 2 | 3 |
| > Length | 3000 | | |
| > Pump | 63 m³ | 100 m³ | 160 m³ |
| > Gas | Inert | Oxygen | |
| > Exit Conveyor | Rollers | Powered chain belt | |
| > Film | Print sensor | Euro hole | |

SPECIFICATIONS THERMOFORMER

	MACHINE LENGHT	MACHINE WIDTH	MACHINE HEIGHT	VOLTAGE*	POWER CONSUMPTION	AIR	WATER
TH 285/320/355	3500	727	1708	400V-3-50Hz	7,5 kW	6 bar 200 Ltr/min	2,1Ltr/min 1,5 bar
TH 420	3500	792	1708	400V-3-50 Hz	7,5 kW	6 bar 200 Ltr/min	2,1Ltr/min 1,5 bar
	FILM THICKNESS	MAX DEPTH					
FLEXIBLE FILM	< 300 µm	95					
RIGID FILM	Ca. 300-400 µm	60					
SKIN PACK	x	20					

Dimensions in mm *Machines can be supplied with all worldwide voltages applicable

MODELS THERMOFORMERS

MODEL	WIDTH	STROKE	LOADING AREA
TH 285-240	285	240	1400
TH 285-270	285	270	1300
TH 285-300	285	300	1100
TH 320-240	320	240	1400
TH 320-270	320	270	1300
TH 320-300	320	300	1100
TH 355-240	355	240	1400
TH 355-270	355	270	1300
TH 355-300	355	300	1100
TH 420-240	420	240	1400
TH 420-270	420	270	1300
TH 420-300	420	300	1100

Dimensions in mm

По вопросам продаж и поддержки обращайтесь:

Алматы (7273)495-231
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курган (3522)50-90-47
Курск (4712)77-13-04
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижегород (831)429-08-12
Новокузнецк (3843)20-46-81
Новосибирск (383)227-86-73
Ноябрьск (3496)41-32-12
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Пермь (342)205-81-47
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саранск (8342)22-96-24
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Улан-Удэ (3012)59-97-51
Ульяновск (8422)24-23-59
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70 Казахстан +7(7172)727-132 Киргизия +996(312)96-26-47

tav@nt-rt.ru || <https://turbovac.nt-rt.ru>